

PFP-25HP-DSL-MR

DIESEL POWERED PUMP

The MR version gives you more pressure to meet the requirements of an initial attack.

Also available in skid version



ENGINE SPECIFICATIONS

- D902 Kubota liquid cooled engine
- 3-cylinder, 4-stroke diesel engine
- Electric start
- 6 gallon (22 l) detachable fuel tank
- Alternator 12V - 40A

PUMP UNIT SPECIFICATIONS

- C.E.T. single stage centrifugal pump
- Pump body made from high resistance aluminum alloy
- Bronze impellers
- Mechanical shaft seal
- Stainless steel pump shaft
- Electric priming system, guaranteed up to 20' (6 meter) lift
- One 1 1/2" (38mm) delivery outlet with Fire Type swing-out valve
- One 2 1/2" (65mm) suction inlet
- Dimensions: Length: 31" (787 mm); Width: 26" (660 mm); Height: 31-1/2" (800 mm).
- Wet weight: 360 lbs (163 kg)


CONTROL PANEL

- Engine start/stop button
- Throttle control lever
- Operating panel light
- Pilot lights
- Pressure gauge
- Vacuum pressure gauge

PERFORMANCE

315 GPM @ 10 PSI
300 GPM @ 50 PSI
230 GPM @ 100 PSI

145 GPM @ 150 PSI
105 GPM @ 175 PSI



LIMITED WARRANTY

- 3 YEARS



ACCEPT ONLY THE BEST



A CENTURY
OF ENGINEERING
FOR THE BRAVEST