

# PFP-6HPHND-M-TWIN

## HONDA POWERED PUMP

The Goliath model is a compact pump that delivers amazing pressure performance so as to meet the needs of several applications.

Also available in skid version



## ENGINE SPECIFICATIONS

- GX200 Honda air cooled engine
- Single cylinder, 4-stroke gasoline engine
- Manual recoil start
- 0.8 gallon (3.1 l) integrated fuel tank

## PUMP UNIT SPECIFICATIONS

- C.E.T. dual stage centrifugal pump
- Pump body made from aluminum
- Aluminum impeller
- Mechanical shaft seal
- Self priming system
- Two 1" (25 mm) delivery outlets and one 1 1/2" (38 mm) NPSH delivery outlet
- One 1 1/2" (38 mm) NPSH suction inlet
- Dimensions (approx.): Length: 19" (483 mm) Width: 17" (406 mm); Height: 16" (381 mm)
- Weight (approx.): 59 lbs (27 kg)


## INCLUDED ACCESSORIES

- Low oil alert.

## PERFORMANCE

70 GPM @ 10 PSI  
65 GPM @ 50 PSI

45 GPM @ 100 PSI  
35 GPM @ 125 PSI



## LIMITED WARRANTY

- 3 YEARS



ACCEPT ONLY THE BEST



A CENTURY  
OF ENGINEERING  
FOR THE BRAVEST