

PFP-9HPHND-EM-TWIN

HONDA POWERED PUMP

The Goliath model is a compact pump that delivers amazing pressure performance so as to meet the needs of several applications.

Also available in skid version



ENGINE SPECIFICATIONS

- GX270 Honda air cooled engine
- Single cylinder, 4-stroke gasoline engine
- 12V electric start with recoil start as backup
- 1.4 gallon (5.3 l) integrated fuel tank
- Charge coil 12V 3A

PUMP UNIT SPECIFICATIONS

- C.E.T. dual stage centrifugal pump
- Pump body made from aluminum
- Aluminum impeller
- Mechanical shaft seal
- Self priming system
- Two 1" (25 mm) delivery outlets and one 1 1/2" (38 mm) NPSH delivery outlet
- One 1 1/2" (38 mm) NPSH suction inlet
- Dimensions: Length: 24-1/2" (620 mm) Width: 19" (480 mm); Height: 18" (460 mm)
- Wet weight: 122 lbs (56 kg)


INCLUDED ACCESSORIES

- Low oil alert

PERFORMANCE

70 GPM @ 10 PSI
60 GPM @ 50 PSI

55 GPM @ 100 PSI
40 GPM @ 125 PSI



LIMITED WARRANTY

- 3 YEARS



ACCEPT ONLY THE BEST



A CENTURY
OF ENGINEERING
FOR THE BRAVEST